

# AWAC - 400 kHz



## Real-time current profiles and directional waves with up to 100 m range

The AWAC 400 kHz ADCP has become the standard reference technology in submerged wave-measurement applications. Thousands of these ADCPs have been deployed to capture the full wave spectrum, in combination with current profiles. With a 100 m maximum range for wave measurements and 1.5 Hz sampling of the surface elevation, the AWAC 400 kHz is the optimal tool for deeper-water current and wave measurements.

# AWAC - 400 kHz



## Highlights

- ✓ Real-time current profiles and waves to 100 m range
- ✓ Acoustic surface tracking (AST) with vertical beam
- ✓ Can be used both with fixed frames and subsurface buoys

## Applications

- ✓ Online measurements of currents and waves
- ✓ Design data for planning of new coastal structures
- ✓ Site studies for offshore wind platforms
- ✓ Coastal erosion studies
- ✓ Measurement campaigns where the full wave spectrum is needed
- ✓ Monitoring of transient waves for channel wall protection
- ✓ Studies of tidal currents

## Technical specifications

### → Water velocity measurements

|                         |                                       |
|-------------------------|---------------------------------------|
| Maximum profiling range | 100 m                                 |
| Cell size               | 1.0-8.0 m                             |
| Number of cells         | Typical 20-40, max. 128               |
| Velocity range          | ±10 m/s horizontal, ±5 m/s along beam |
| Accuracy                | ±1% of measured value ±0.5 cm/s       |
| Velocity precision      | Consult instrument software           |
| Maximum output rate     | 1 Hz                                  |
| Internal sampling rate  | 2 Hz                                  |

### → Echo intensity (along slanted beams)

|                               |  |
|-------------------------------|--|
| Sampling                      | Same as velocity   |
| Resolution                    | 0.45 dB  |
| Dynamic range                 | 90 dB  |
| Transducer acoustic frequency | 400 kHz, 600 kHz for vertical beam   |
| Number of beams               | 3 beams 120° apart, one vertical beam, (90° apart, one at 5° for platform mount) |
| Beam width                    | 2.4°   |
| Beam width vertical beam      | 1.7°   |

### → Wave measurement option (AST)

|                                 |   |
|---------------------------------|---|
| Maximum depth                   | 100 m                                       |
| Data types                      | Pressure, one velocity along each beam, AST |
| Sampling rate velocity (output) | 0.75 Hz                                     |
| Sampling rate AST (output)      | 1.5 Hz                                      |
| No. of samples per burst        | 512, 1024 or 2048                           |

### → Wave estimates

|                           |  |
|---------------------------|--|
| Range                     | -15 to 15 m  |
| Accuracy/resolution (Hs)  | < 1% of measured value / 1 cm                                  |
| Accuracy/resolution (Dir) | 2° / 0.1°  |
| Period range              | 1-50 s   |
| Cut-off period (Hs)       | 20 m depth: 0.9 sec, 60 m depth: 1.5 sec, 100 m depth: 2 sec   |
| Cut-off period (dir)      | 20 m depth: 3.1 sec, 60 m depth: 5.5 sec, 100 m depth: 7.1 sec |

### → Sensors

|              |                                |
|--------------|--------------------------------|
| Temperature: | Thermistor embedded in housing |
| Temp. range  | -4 to +40 °C                   |

# AWAC - 400 kHz



## → Sensors

|                           |  |
|---------------------------|--|
| Temp. accuracy/resolution | 0.1 °C/0.01 °C                                   |
| Temp. time response       | < 5 min  |
| Compass:                  | Magnetoresistive                                 |
| Accuracy/resolution       | 2°/0.1° for tilt < 15°                           |
| Tilt:                     | Liquid level                                     |
| Accuracy/resolution       | 0.2°/0.1°  |
| Maximum tilt              | 30°, AST requires < 10° instrument tilt          |
| Up or Down                | Automatic detect                                 |
| Pressure:                 | Piezoresistive                                   |
| Range                     | 100 m  |
| Accuracy                  | 0.5% of full scale (optional 0.1% of full scale) |
| Resolution                | 0.005% of full scale                             |

## → Analog inputs

|   |  |
|---|--|
| No. of channels                         | 2  |
| Supply voltage to analog output devices | Three options selectable through firmware commands: 1) Battery voltage/500 mA, 2) +5 V/250 mA, 3) +12 V/100 mA |
| Voltage input                           | 0-5 V  |
| Resolution                              | 16-bit A/D   |

## → Data recording

|                |  |
|----------------|--|
| Capacity       | 9 MB standard, 4/16 GB (ProLog)                  |
| Profile record | Ncells*9 + 120 bytes                             |
| Wave record    | Nsamples*24 + 1k bytes                           |
| Mode           | Stop when full (default and Prolog) or wrap mode |

## → Real-time clock

|                            |             |
|----------------------------|-------------|
| Accuracy                   | ±1 min/year |
| Backup in absence of power | 1 year      |

## → Data communications

|                             |  |
|-----------------------------|--|
| I/O                         | RS-232 or RS-422. Software supports most commercially available USB– RS-232 converters |
| Communication baud rate     | 300-115200 Bd  |
| Recorder download baud rate | 600/1200 kBd for both RS-232 and RS-422  |
| User control                | Handled via "AWAC AST" software, or ActiveX®controls. "Seastate" for online systems    |
| Output formats              | NMEA, Binary. Prolog provides same types also for processed wave and current data      |

## → Connectors

# AWAC - 400 kHz



|   |   |
|---|---|
| Bulkhead  | MCBH-2-FS, MCBH-8-FS, optional Souriau M-series metal connector for online use              |
| Cable   | PMCIL-8-MP on 10 m polyurethane cable   |
| —> Software   |   |
| Functions   | Deployment planning, instrument configuration, data retrieval and conversion (for Windows®) |
| —> Power  |   |
| DC input  | 9-18 V DC   |
| Maximum peak current  | 3 A   |
| Avg. power consumption  | 0.23 W  |
| Sleep current   | < 100 $\mu$ A   |
| Transmit Power  | 1-30 W, 3 adjustable levels   |
| —> Environmental  |   |
| Operating temperature   | -4 to +40 °C  |
| Storage temperature   | -20 to +60 °C   |
| Shock and vibration   | IEC 721-3-2   |
| EMC approval  | IEC 61000   |
| Depth rating  | 300 m   |
| —> Materials  |   |
| Standard model  | Delrin® and polyurethane plastics with titanium screws                                      |
| —> Dimensions   |   |
| Maximum diameter  | 306 mm  |
| Maximum length  | 203 mm  |
| —> Weight   |   |
| Weight in air   | 7.3 kg  |
| Weight in water   | 3.6 kg  |
| —> Online cable   |   |
| Polyurethane jacket, Shore D hardness, 13 mm in diameter, max 2 km. Inquire for longer cables |   |